

Tabla de especificaciones

Dimensiones (mm)

Código ACDelco®	Línea	Peso (kg)	C 20 (Ah)	RC (min)	CCA (A)	Largo	Ancho	Alto	
B045DVL1	ACDelco White	11.2	45	60	300	210	175	175	
B045EVL1		11.2	45	60	300	210	175	175	
B060DVL1		13.1	60	80	375	244	175	175	
B060EVL1		13.1	60	80	375	244	175	175	
B070DVL1		16.4	70	110	620	283	175	175	
B070EVL1		16.4	70	110	620	283	175	175	
11A045D1	ACDelco Red	11.0	45	65	320	210	175	175	
11A045E1		11.0	45	65	320	210	175	175	
11A047D1		14.0	47	70	425	237	129	227	
11A055D1		13.2	55	85	425	244	175	175	
11A055E1		13.2	55	85	425	244	175	175	
11A063D1		15.2	63	105	500	281	175	175	
11A063E1		15.2	63	105	500	281	175	175	
11A070D1		16.5	70	115	620	281	175	175	
11A070E1		16.5	70	115	620	281	175	175	
11A075D1		17.9	75	105	530	273	170	226	
11A075E1		17.9	75	105	530	273	170	226	
11A090D1		23.1	90	160	700	360	177	190	
11A100E2		25.3	100	165	640	330	172	241	
11A135D3		39.0	135	240	770	510	213	236	
11A150D3		41.0	150	270	850	510	213	236	
11A170D3		43.7	170	300	1000	510	213	236	
11B045D1	ACDelco Gold	11.9	45	65	375	210	175	175	
11B045E1		11.9	45	65	375	210	175	175	
11B055D1		13.9	55	85	425	244	175	175	
11B055E1		13.9	55	85	425	244	175	175	
11B060D1		14.5	60	90	480	244	175	175	
11B060E1		14.5	60	90	480	244	175	175	
11B065D1		17.8	65	115	620	281	175	175	
11B065E1		17.8	65	115	620	281	175	175	
11B070D1		18.3	70	115	660	281	175	175	
11B070E1		18.3	70	115	660	281	175	175	
11B100E2		26.5	100	180	750	330	172	241	
11B135D3		39.0	135	240	770	510	213	236	
11B150D3		41.0	150	270	950	510	213	236	
11B170D3		43.7	170	330	1000	510	213	236	
11E11501			26.5	115*	180	750	330	172	241

C20: Capacidad Nominal.

RC: Capacidad de Reserva.

CCA: Corriente de Arranque.

*100 - hour capacity.